

TR 136 - Technical Specifications



Description

TR 136 has been developed by BKT to equip tractors and trailers in soil tillage and haulage operations. This tire provides improved traction in all working conditions along with best cut and chip resistance to reduce machine downtime and increase your productivity. Thanks to the increased number of lugs, TR 136 provides outstanding traction even at high loads.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor • Trailer

Version	STANDARD
Type	TT
Tyre Size	18.4 - 30
LI/SS	139 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	467
Overall Diameter (mm)	1550
Static Loaded Radius (mm)	712
Rolling Circumference (mm)	4719
SRI (mm)	725
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-004473
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.40
30	2430

Printed on 5/5/2024 12:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..