

## TR 318 - Data Sheet



### Description

TR 318 is specifically designed for sprayers and implement machinery. Its dual-angled lugs provide excellent traction and outstanding driving comfort. TR 318 also features extraordinary self-cleaning properties.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Sprayer

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
23 X 9.00 - 12	STANDARD	93 A3	6	7.0		220	585	TT	E11-106R-004521
23 X 9.00 - 12	STANDARD	93 A3	6	7.0		220	585	TL	E11-106R-004521
26 X 10.00 - 12	STANDARD	107 A3	8	8.5		265	675	TT	E11-106R-004522

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 12:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..