

TR 360 - Data Sheet



Description

TR 360 is suitable for implement machinery in on-and-off-the-road transport as well as lawn and garden applications. The particular tread design along with the casing structure ensures a long tire life-cycle.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Implement Machinery

SIZE	Version	USACode	LI/SS DRIVE WHEEL	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 7 - 8	STANDARD	94013104		6	5.5		7.1	18.1	8	52.5	TL	E4-106R-002184
240/70 - 15 (28X9.00 - 15)	STANDARD	94075416	115 A8	8	7.00 I	6 ½ K	9.3	29.1	0	0	TL	E11-106R-008778

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 8:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..