

## TR 387 - Technical Specifications



### Description

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer  
Industrial: Compactor

Version	STANDARD
Type	TL
Tyre Size	16.9 - 28
LI/SS	131 A8

## Dimensions US Standard

Usa code	94004966
Ply Rating	8
Section Width (inch)	17.3
Overall Diameter (inch)	55.1
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	160.4
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-005278
TRA Code	R3

## Load capacity (lbs)

mph / psi	24
25	4300

Printed on 4/24/2024 10:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..