TR 387 - Technical Specifications

Description

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Trailer
Industrial: Compactor

Version	STANDARD
Type	TL
Tyre Size	23.1 - 26
LI/SS	153 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	592
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4688
SRI (mm)	750
Rim Rec	DW 20 B
ECE	E4-106R-002317
TRA Code	R3

Load capacity (Kg)

km/h / bar	1.70
30	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 5:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..