

TR 459 - Technical Specifications



Description

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Backhoe Loader • Tractor
Industrial: Backhoe Loader

Version	INDUSTRIAL
Type	TL
Tyre Size	21L - 24
LI/SS	157 A8

Dimensions US Standard

Usa code	94054404
Ply Rating	14
Section Width (inch)	21
Overall Diameter (inch)	54.3
Static Loaded Radius (inch)	23.8
Rolling Circumference (inch)	157.3
Rim Rec	DW 18 L
ECE	E11-106R-005366
TRA Code	R4

Load capacity (lbs)

mph / psi	36
25	9090

Printed on 4/28/2024 2:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..