

TR 882 - Data Sheet



Description

TR 882 is a very versatile tire suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tire features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer
Industrial: Trailer

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
400/60 - 15.5	ARAMID BELTED	132 A8	145 A8	14	AG 13.00		400	875	378	2605	410	TL	E11-106R-004331
400/60 - 15.5	ARAMID BELTED HD	137 A8	149 A8	18	AG 13.00		400	875	378	2605	410	TL	E11-106R-005354
400/60 - 15.5	HD	132 A8	145 A8	14	AG 13.00		400	875	378	2605	410	TL	E4-106R-001879
400/60 - 15.5	HD	137 A8	149 A8	18	AG 13.00		400	875	378	2605	410	TL	
400/60 - 15.5	SPECIAL	132 A8	145 A8	14	AG 13.00		400	875	378	2605	410	TL	E11-106R-004332
400/60 - 15.5	SPECIAL	137 A8	149 A8	18	AG 13.00		400	875	378	2605	410	TL	E11-106R-004334
400/60 - 15.5	STANDARD	122 A8	134 A8	8	AG 13.00		400	875	378	2605	410	TL	E11-106R-004330
400/60 - 15.5	STANDARD	132 A8	145 A8	14	AG 13.00		400	875	378	2605	410	TL	E4-106R-001879
400/60 - 15.5	STANDARD	137 A8	149 A8	18	AG 13.00		400	875	378	2605	410	TL	E4-106R-001878

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/13/2025 4:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..