

TR 882 - Data Sheet



Description

TR 882 is a very versatile tire suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tire features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer
Industrial: Trailer

| SIZE | Version | USACode | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|------------------|----------|-------------------|--------------------|----|----------|---------|------|------|------|-------|------|-----------------|
| 400/60 - 15.5 | ARAMID BELTED | 94030101 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004331 |
| 400/60 - 15.5 | ARAMID BELTED HD | 94048304 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-005354 |
| 400/60 - 15.5 | HD | 94034529 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E4-106R-001879 |
| 400/60 - 15.5 | HD | 94030934 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | |
| 400/60 - 15.5 | SPECIAL | 94019915 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004332 |
| 400/60 - 15.5 | SPECIAL | 94029006 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004334 |
| 400/60 - 15.5 | STANDARD | 94019830 | 122 A8 | 134 A8 | 8 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E11-106R-004330 |
| 400/60 - 15.5 | STANDARD | 94019861 | 132 A8 | 145 A8 | 14 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E4-106R-001879 |
| 400/60 - 15.5 | STANDARD | 94019908 | 137 A8 | 149 A8 | 18 | AG 13.00 | | 15.7 | 34.4 | 14.9 | 102.6 | TL | E4-106R-001878 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 1:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..