

TRAC FARM - Technical Specifications



Description

TRAC FARM is a heavy-duty tire specifically designed for tractors in soil tillage and haulage applications. Its deep tread and the special cut-and-chip-resistant compound make the tire suitable for the most difficult operating conditions, ensuring the best return on investment during the entire product life-cycle. TRAC FARM has been designed with more lugs providing extraordinary traction and self-cleaning properties.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	11.2 - 20
LI/SS	107 A8

Dimensions US Standard

Usa code	94043415
Ply Rating	8
Section Width (inch)	11.4
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	18.2
Rolling Circumference (inch)	115.7
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-003561
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	2150

Printed on 4/27/2024 11:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..