

## TRAC GRADER + - Technical Specifications



### Description

TRAC GRADER + (G-2) is a bias-ply tire for graders. It is an excellent choice for the budget-minded customers. The durable casing is designed to last. The self-cleaning tread design shows open lug-to-void-ratio which provides best traction in all conditions. Its "special" version is made of a special cut-and-chip-resistant compound.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Grader

|           |            |
|-----------|------------|
| Version   | STANDARD   |
| Type      | TT         |
| Tyre Size | 14.00 - 24 |

## Dimensions US Standard

|                              |                              |
|------------------------------|------------------------------|
| Usa code                     | 94059768                     |
| Ply Rating                   | 16                           |
| Overall Width (inch)         | 14.3                         |
| Overall Diameter (inch)      | 53.1                         |
| Static Loaded Radius (inch)  | 23.5                         |
| Rolling Circumference (inch) | 157.1                        |
| Rim Rec                      | 8.00 TG SDC                  |
| Rim Alt                      | 9.00/1.5 (DC) ; 10.00/VA SDC |
| TRA Code                     | G2                           |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 51   |
| 25        | 8050 |

Printed on 4/26/2024 11:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..