



XL GRIP (G3) - Data Sheet



Description

XL GRIP (G-3) is a bias-ply tire for graders designed to minimize cuts and punctures in heavy-duty grading environments where exceptional traction is required.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Grader

| SIZE | Version | TRA Code | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | SRI | Type |
|-------------------|----------|----------|----|--------------|------------------------------|-----|------|-----|------|-----|------|
| 13.00 - 24 | STANDARD | G3 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 350 | 1295 | 601 | 3872 | | TL |
| 13.00 - 24 | STANDARD | G3 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 350 | 1295 | 601 | 3872 | | TT |
| 14.00 - 24 | STANDARD | G3 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 365 | 1345 | 617 | 4002 | | TL |
| 14.00 - 24 | STANDARD | G3 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 365 | 1345 | 617 | 4002 | | TT |
| 16.00 - 24 (-) | STANDARD | G3 | 16 | 10.00 VA SDC | - | 432 | 1450 | 654 | 4289 | - | TL |
| 18.00 - 25 | STANDARD | G3 | 32 | 13.00/2.5 | 15.00/2.5 | 510 | 1615 | 739 | 4780 | | TL |
| 18.00 - 25 | STANDARD | G3 | 40 | 13.00/2.5 | 15.00/2.5 | 510 | 1615 | 739 | 4780 | | TL |

Printed on 4/27/2024 12:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..