

AGRI TRAILER - Technische Daten



Description

AGRI TRAILER wurde speziell für Traktorenanhänger entwickelt. Der Reifen ist ideal für die moderne Landwirtschaft und eignet sich für Transportwendungen auf und abseits der Straße. Seine robuste Konstruktion zeigt sich in hoher Tragfähigkeit, während das extra tiefe Laufflächenprofil eine bessere Kilometerleistung sowie ein längeres Reifenleben bietet.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	286
Overall Diameter (mm)	1080
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (Kg)

km/h / bar	9.30	8.60
30 LS	3845	-
30 LD	-	3405

Printed on 19.04.2024 20:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..