

## AGRIMAX ELOS - Technische Daten



### Description

AGRIMAX ELOS wurde für maximale Traktionsleistung auch unter besonders harten Bedingungen auf nassem Land, wie z.B. auf Reisfeldern und Sumpfboden, entworfen. Das Reifenprofil wurde speziell entwickelt, um ausgezeichnete Selbstreinigungseigenschaften zu bieten - unverzichtbar beim Einsatz auf schlammigen Böden und beim Transfer. Zur Optimierung der Produktivität des Landwirtschaftsbetriebes durch geringere Stillstandzeiten wurde der Agrimax Elos Reifen mit integrierten Seitenwandprotektoren entworfen, die jederzeit maximalen Schutz vor eventuellen Beschädigungen bieten.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 480/80 R 38<br>(18.4 R 38) |
| LI/SS     | 149 A8/B                   |

## Dimensions International Standard

|                            |                  |
|----------------------------|------------------|
| Section Width (mm)         | 489              |
| Overall Diameter (mm)      | 1803             |
| Static Loaded Radius (mm)  | 821              |
| Rolling Circumference (mm) | 5356             |
| SRI (mm)                   | 825              |
| Rim Rec                    | W 16 L           |
| Rim Alt                    | W 15 L ; DW 16 L |
| ECE                        | E11-106R-002991  |
| TRA Code                   | R2               |

## Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 40         | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 30         | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |
| 10 LT      | 2400 | 2790 | 3180 | 3575 | 3965 | 4355 |
| 10 HT      | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |

Printed on 24.04.2024 17:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..