

## AGRIMAX ELOS - Technische Daten



### Description

AGRIMAX ELOS wurde für maximale Traktionsleistung auch unter besonders harten Bedingungen auf nassem Land, wie z.B. auf Reisfeldern und Sumpfboden, entworfen. Das Reifenprofil wurde speziell entwickelt, um ausgezeichnete Selbstreinigungseigenschaften zu bieten - unverzichtbar beim Einsatz auf schlammigen Böden und beim Transfer. Zur Optimierung der Produktivität des Landwirtschaftsbetriebes durch geringere Stillstandzeiten wurde der Agrimax Elos Reifen mit integrierten Seitenwandprotektoren entworfen, die jederzeit maximalen Schutz vor eventuellen Beschädigungen bieten.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 38
LI/SS	178 A8/B

## Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	2019
Static Loaded Radius (mm)	915
Rolling Circumference (mm)	6103
SRI (mm)	925
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-004896
TRA Code	R2

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
50	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
40	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
30	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025
10 LT	3720	4325	4925	5630	6235	6835	7540	7940	8745	9450	10050
10 HT	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025

Printed on 24.04.2024 22:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..