AGRIMAX FORCE - Technische Daten

Description

AGRIMAX FORCE, das Spitzenprodukt von BKT, ist ein Radialreifen, der speziell zur Bodenbearbeitung, sowie Transport- und Ernteanwendungen mit Hochleistungstraktoren und Erntemaschinen entwickelt wurde. Dabei bietet er ein hervorragendes Arbeitspotenzial sowie effiziente Leistungen. Dank der IF-Technologie kann dieser Reifen schwere Lasten bei geringerem Reifendruck im Vergleich zu einem Standardreifen bei reduzierter Bodenverdichtung tragen. AGRIMAX FORCE hat einen verstärkten Wulst und wartet mit erstklassiger Traktion, ausgezeichneten Selbstreinigungseigenschaften und Kraftstoffersparnis neben einem komfortablen Fahrerlebnis auf.

UM

International Standard

Construction

RADIAL

Machinery

Landwirtschaft: Erntemaschine • Hochleistungstraktor

Version	STANDARD
Type	TL
Tyre Size	IF 480/95 R 50
LI/SS	170 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	2170
Static Loaded Radius (mm)	1002
Rolling Circumference (mm)	6574
SRI (mm)	1025
Rim Rec	DW 16 B
ECE	E11-106R-004898
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2565	2945	3385	3820	4255	4695	5130	5460
From 65 to 40	2820	3240	3720	4200	4680	5160	5640	6000
30	2930	3365	3865	4365	4865	5365	5865	6240
20	3045	3495	4015	4535	5050	5570	6090	6480
10	3580	4110	4720	5330	5940	6550	7160	7620
***Upto 10 Cyc with front loader**	3945	4535	5205	5880	6550	7220	7895	8400
10HT	2930	3365	3865	4365	4865	5365	5865	6240

*** *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.**

Printed on 25.04.2024 21:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..