

AGRIMAX RT 657 - Technische Daten



Description

AGRIMAX RT 657 ist der ideale Reifen für die Bodenbearbeitung und den Einsatz auf der Straße; einige Größen sind auch zur Weinernte geeignet. Der Reifen bietet hervorragenden Fahrkomfort sowie deutliche Kraftstoffersparnis. Agrimax RT 657 ist die beste Wahl, für alle, die einen vielseitigen und zuverlässigen Reifen brauchen, ohne die Performance zu beeinträchtigen.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Traktor • Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	320/65 R 18
LI/SS	109 A8/B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	873
Static Loaded Radius (mm)	392
Rolling Circumference (mm)	2587
SRI (mm)	410
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E4-106R-000636
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	600	695	785	870	950	1030
40	600	695	785	870	950	1030
30	645	745	840	930	1020	1105
10 LT	805	930	1055	1165	1275	1385
10 HT	645	745	840	930	1020	1105

Printed on 03.03.2024 04:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..