

## AGRIMAX RT 657 - Technische Daten



### Description

AGRIMAX RT 657 ist der ideale Reifen für die Bodenbearbeitung und den Einsatz auf der Straße; einige Größen sind auch zur Weinernte geeignet. Der Reifen bietet hervorragenden Fahrkomfort sowie deutliche Kraftstoffersparnis. Agrimax RT 657 ist die beste Wahl, für alle, die einen vielseitigen und zuverlässigen Reifen brauchen, ohne die Performance zu beeinträchtigen.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor • Traubenerntemaschine

Version	SPECIAL
Type	TL
Tyre Size	440/65 R 24
LI/SS	135 D/138 A8

## Dimensions US Standard

Usa code	94053711
Section Width (inch)	17.4
Overall Diameter (inch)	46.5
Static Loaded Radius (inch)	21.2
Rolling Circumference (inch)	139.6
Rim Rec	W 14 L
Rim Alt	W 13 ; W 15 L
ECE	E4-106R-000616
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	2310	2700	3030	3370	3700	3990	4430	4810
30	2420	2830	3190	3540	3890	4200	4650	5050
25	2500	2920	3280	3650	4010	4320	4790	5200
20	2660	3110	3490	3880	4270	4600	5090	5530
5 LT	3100	3620	4070	4520	4970	5360	5940	6450
5 HT	2660	3110	3490	3880	4270	4600	5090	5530

Printed on 25.04.2024 19:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..