

AGRIMAX RT 657 - Technische Daten



Description

AGRIMAX RT 657 ist der ideale Reifen für die Bodenbearbeitung und den Einsatz auf der Straße; einige Größen sind auch zur Weinernte geeignet. Der Reifen bietet hervorragenden Fahrkomfort sowie deutliche Kraftstoffersparnis. Agrimax RT 657 ist die beste Wahl, für alle, die einen vielseitigen und zuverlässigen Reifen brauchen, ohne die Performance zu beeinträchtigen.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Traktor • Traubenerntemaschine

| | |
|-----------|--------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 540/65 R 30 |
| LI/SS | 150 D/153 A8 |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 530 |
| Overall Diameter (mm) | 1464 |
| Static Loaded Radius (mm) | 670 |
| Rolling Circumference (mm) | 4403 |
| SRI (mm) | 700 |
| Rim Rec | W 16 L |
| Rim Alt | W 18 L |
| ECE | E4-106R-000651 |
| TRA Code | R1W |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1610 | 1880 | 2115 | 2345 | 2580 | 2785 | 3085 | 3350 |
| 50 | 1690 | 1975 | 2220 | 2465 | 2715 | 2925 | 3240 | 3520 |
| 40 | 1755 | 2045 | 2300 | 2555 | 2815 | 3030 | 3360 | 3650 |
| 30 | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |
| 10 LT | 2160 | 2515 | 2830 | 3145 | 3460 | 3730 | 4135 | 4490 |
| 10 HT | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |

Printed on 26.04.2024 00:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..