

## AGRIMAX RT 657 - Technische Daten



### Description

AGRIMAX RT 657 ist der ideale Reifen für die Bodenbearbeitung und den Einsatz auf der Straße; einige Größen sind auch zur Weinernte geeignet. Der Reifen bietet hervorragenden Fahrkomfort sowie deutliche Kraftstoffersparnis. Agrimax RT 657 ist die beste Wahl, für alle, die einen vielseitigen und zuverlässigen Reifen brauchen, ohne die Performance zu beeinträchtigen.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Traktor • Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	540/65 R 30
LI/SS	150 D/153 A8

## Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1464
Static Loaded Radius (mm)	670
Rolling Circumference (mm)	4403
SRI (mm)	700
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000651
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1610	1880	2115	2345	2580	2785	3085	3350
50	1690	1975	2220	2465	2715	2925	3240	3520
40	1755	2045	2300	2555	2815	3030	3360	3650
30	1855	2160	2430	2700	2970	3200	3550	3855
10 LT	2160	2515	2830	3145	3460	3730	4135	4490
10 HT	1855	2160	2430	2700	2970	3200	3550	3855

Printed on 25.04.2024 17:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..