AGRIMAX RT 657 - Datenblatt

Description

AGRIMAX RT 657 ist der ideale Reifen für die Bodenbearbeitung und den Einsatz auf der Straße; einige Größen sind auch zur Weinernte geeignet. Der Reifen bietet hervorragenden Fahrkomfort sowie deutliche Kraftstoffersparnis. Agrimax RT 657 ist die beste Wahl, für alle, die einen vielseitigen und zuverlässigen Reifen brauchen, ohne die Performance zu beeinträchtigen.

UM

US Standard

Construction

RADIAL

Machinery

Landwirtschaft: Traktor • Traubenerntemaschine

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
320/65 R 16	STANDARD	94042036	R1W	117 D/120 A8	W 10	W 9 ; W 11	12.6	32.4	14.4	97.1	TL	0	E4-106R-001815
320/65 R 18	STANDARD	94027606	R1W	109 A8/B	W 10	W 9 ; W 11	12.6	34.4	15.4	101.9	TL	0	E4-106R-000636
320/65 R 18	STANDARD	94073252	R1W	125 A8/B	W 10	W 9 ; W 11	12.2	34.8	15.7	105	TL	0	E11-106R-008145
340/65 R 18	STANDARD	94039203	R1W	113 A8/B	W 11	W 10 ; W 12	13.5	35.4	15.7	105	TL	0	E4-106R-001816
340/65 R 20	STANDARD	94042005	R1W	124 D/127 A8	W 11	W 10 ; W 12	13.5	37.4	16.9	113.9	TL	0	E4-106R-001413
420/65 R 20	STANDARD	94041862	R1W	135 D/138 A8	W 13	W 11 ; W 12	16.5	41.5	18.4	124.5	TL	0	E4-106R-001390
440/65 R 20	STANDARD	94042753	R1W	138 D/141 A8	W 14 L	W 13 ; W 15 L	17.4	42.5	18.9	127.6	TL	0	E4-106R-000760
420/65 R 24	STANDARD	94042562	R1W	138 D/141 A8	W 13	W 11 ; W 12	16.5	45.5	20.4	136.5	TL	0	E4-106R-000761
440/65 R 24	SPECIAL	94053711	R1W	135 D/138 A8	W 14 L	W 13 ; W 15 L	17.4	46.5	21.2	139.6	TL	0	E4-106R-000616
440/65 R 24	STANDARD	94029136	R1W	135 D/138 A8	W 14 L	W 13 ; W 15 L	17.4	46.5	21.2	139.6	TL	0	E4-106R-000616
480/65 R 24	SPECIAL	94062621	R1W	140 D/143 A8	W 15 L	W 14 L	18.9	48.6	22.1	146.9	TL	1	E4-106R-000617
480/65 R 24	STANDARD	94028528	R1W	140 D/143 A8	W 15 L	W 14 L	18.9	48.6	22.1	146.9	TL	0	E4-106R-000617
540/65 R 24	SPECIAL	94066636	R1W	146 D/149 A8	W 16 L	W 18 L	20.9	51.7	23.2	154.7	TL	0	E4-106R-000773
540/65 R 24	STANDARD	94028658	R1W	146 D/149 A8	W 16 L	W 18 L	20.9	51.7	23.2	154.7	TL	0	E4-106R-000773
420/65 R 28	STANDARD	94052394	R1W	135 D/138 A8	W 13	W 12 ; W 11	16.5	49.5	23	150.6	TL	0	E11-106R-002974
440/65 R 28	STANDARD	94029143	R1W	138 D/141 A8	W 14 L	W 13 ; W 15 L	17.4	50.5	23.2	154.6	TL	0	E4-106R-000767
480/65 R 28	STANDARD	94028535	R1W	142 D/145 A8	W 15 L	W 14 L	18.9	52.6	24	161.1	TL	0	E4-106R-000653
540/65 R 28	SPECIAL	94056927	R1W	149 D/152 A8	W 16 L	W 18 L	20.9	55.6	25.3	167.4	TL	0	E4-106R-000650
540/65 R 28	STANDARD	94021376	R1W	149 D/152 A8	W 16 L	W 18 L	20.9	55.6	25.3	167.4	TL	0	E4-106R-000650
600/65 R 28	SPECIAL	94066025	R1W	154 D/157 A8	DW 20 B	W 18 L	24.1	58.7	26.4	176	TL	0	E4-106R-000621
600/65 R 28	STANDARD	94032129	R1W	154 D/157 A8	DW 20 B	W 18 L	24.1	58.7	26.4	176	TL	0	E4-106R-000621
420/65 R 30	STANDARD	94052899	R1W	136 D/139 A8	W 13	W 12 ; W 11	16.5	51.5	23.9	155.6	TL	0	E11-106R-002975
540/65 R 30	SPECIAL	94056934	R1W	150 D/153 A8	W 16 L	W 18 L	20.9	57.6	26.4	173.3	TL	0	E4-106R-000651
540/65 R 30	STANDARD	94029150	R1W	150 D/153 A8	W 16 L	W 18 L	20.9	57.6	26.4	173.3	TL	0	E4-106R-000651
600/65 R 30	STANDARD	94032310	R1W	155 D/158 A8	DW 20 B	W 18 L	24.1	60.7	27.4	181.5	TL	0	E4-106R-001825
540/65 R 34	SPECIAL	94062645	R1W	152 D/155 A8	W 16 L	W 18 L	20.9	61.7	28	186.7	TL	1	E4-106R-000652
540/65 R 34	STANDARD	94028412	R1W	152 D/155 A8	W 16 L	W 18 L	20.9	61.7	28	186.7	TL	0	E4-106R-000652
600/65 R 34	SPECIAL	94062638	R1W	157 D/160 A8	DW 20 B	W 18 L	24.1	64.7	29.2	195.3	TL	1	E4-106R-001405
600/65 R 34	STANDARD	94032327	R1W	157 D/160 A8	DW 20 B	W 18 L	24.1	64.7	29.2	195.3	TL	0	E4-106R-001405
540/65 R	SPECIAL	94062652	R1W	153 D/156	W 16 L	W 18 L	20.9	65.6	29.9	199.2	TL	1	E4-106R-

38				A8									000589
540/65 R 38	STANDARD	94029167	R1W	153 D/156 A8	W 16 L	W 18 L	20.9	65.6	29.9	199.2	TL	0	E4-106R-000589
600/65 R 38	SPECIAL	94066612	R1W	159 D/162 A8	DW 20 B	W 18 L	24.1	68.7	31.1	206.6	TL	0	E4-106R-000623
600/65 R 38	STANDARD	94032334	R1W	159 D/162 A8	DW 20 B	W 18 L	24.1	68.7	31.1	206.6	TL	0	E4-106R-000623
650/65 R 38	STANDARD	94021383	R1W	163 D/166 A8	DW 20 B	DW 21 B ; DW 23 B	25.4	71.3	32.7	215.9	TL	0	E4-106R-000624
650/65 R 38	STANDARD	94074853	R1W	178 A8/175 B	DW 20 B	DW 21 B ; DW 23 B	25.4	71.5	32.6	216.1	TL	0	E11-106R-008886
900/55 R 38	STANDARD	94067534	R1W	179 D/181 A8	DW 27 B	DW 30 B	34.6	76.8	34.6	230	TL	0	E11-106R-006946
650/65 R 42	STANDARD	94029501	R1W	165 D/168 A8	DW 20 B	DW 21 B ; DW 23 B	25.4	75.3	34.6	228.7	TL	0	E4-106R-000625

Printed on 20.04.2024 16:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..