

## AGRIMAX RT 855 - Technische Daten



### Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Feldspritze • Traktor •  
Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	180/95 R 16 (6.50 R 16)
LI/SS	105 A8/B

## Dimensions International Standard

Section Width (mm)	185
Overall Diameter (mm)	760
Static Loaded Radius (mm)	340
Rolling Circumference (mm)	2265
SRI (mm)	350
Rim Rec	5.5 F
Rim Alt	6.0 F
ECE	E4-106R-000756
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	430	550	670	735	790	865	925	-
40	430	550	670	735	790	865	925	-
30	460	585	715	785	845	925	990	-
10	505	655	795	950	1085	1130	1255	1390

Printed on 24.04.2024 06:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..