

AGRIMAX RT 855 - Technische Daten



Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor • Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	210/90 R 20 (8.3 R 20)
LI/SS	110 A8/B

Dimensions International Standard

Section Width (mm)	211
Overall Diameter (mm)	890
Static Loaded Radius (mm)	412
Rolling Circumference (mm)	2681
SRI (mm)	425
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001817
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	500	575	660	745	830	915	990	1060
40	500	575	660	745	830	915	990	1060
30	535	615	705	795	890	980	1060	1135
10 LT	670	770	885	1000	1115	1230	1330	1425
10 HT	535	615	705	795	890	980	1060	1135

Printed on 24.04.2024 11:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..