

AGRIMAX RT 855 - Technische Daten



Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor • Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	320/85 R 24 (12.4 R 24)
LI/SS	122 A8/B

Dimensions US Standard

Usa code	94021550
Section Width (inch)	13
Overall Diameter (inch)	45.4
Static Loaded Radius (inch)	19.3
Rolling Circumference (inch)	134.8
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000613
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1820	2120	2410	2710	3010	3300
25	1820	2120	2410	2710	3010	3300
20	1950	2270	2590	2910	3230	3540
5 LT	2450	2840	3240	3640	4030	4430
5 HT	1950	2270	2590	2910	3230	3540

Printed on 24.04.2024 03:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..