AGRIMAX RT 855 - Technische Daten

Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

UM

US Standard

Construction

RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor • Traubenerntemaschine

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 36 (12.4 R 36)
LI/SS	128 A8/B

Dimensions US Standard

Usa code	94033065
Section Width (inch)	13
Overall Diameter (inch)	57.4
Static Loaded Radius (inch)	26.5
Rolling Circumference (inch)	173.4
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000762
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2180	2550	2900	3260	3620	3970
25	2180	2550	2900	3260	3620	3970
20	2350	2730	3110	3490	3880	4250
5 LT	2930	3420	3890	4380	4850	5320
5 HT	2350	2730	3110	3490	3880	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 05:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..