

AGRIMAX RT 855 - Technische Daten



Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor •
Traubenerntemaschine

Version	SPECIAL
Type	TL
Tyre Size	340/85 R 24 (13.6 R 24)
LI/SS	125 A8/B

Dimensions US Standard

Usa code	94043972
Section Width (inch)	13.9
Overall Diameter (inch)	46.8
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	139.4
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000604
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2010	2340	2660	2990	3320	3640
25	2010	2340	2660	2990	3320	3640
20	2150	2500	2850	3210	3560	3900
5 LT	2690	3130	3570	4010	4450	4880
5 HT	2150	2500	2850	3210	3560	3900

Printed on 24.04.2024 04:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..