

AGRIMAX RT 855 - Technische Daten



Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor •
Traubenerntemaschine

Version	SPECIAL
Type	TL
Tyre Size	340/85 R 38 (13.6 R 38)
LI/SS	133 A8/B

Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1543
Static Loaded Radius (mm)	712
Rolling Circumference (mm)	4668
SRI (mm)	750
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000766
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1135	1320	1505	1690	1875	2060
40	1135	1320	1505	1690	1875	2060
30	1215	1415	1610	1810	2010	2205
10 LT	1525	1770	2020	2270	2520	2765
10 HT	1215	1415	1610	1810	2010	2205

Printed on 24.04.2024 04:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..