

AGRIMAX RT 855 - Technische Daten



Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor • Traubenerntemaschine

Version	SPECIAL
Type	TL
Tyre Size	420/85 R 34 (16.9 R 34)
LI/SS	142 A8/B

Dimensions US Standard

Usa code	94033133
Section Width (inch)	17.2
Overall Diameter (inch)	62.1
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	185.1
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-000656
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3220	3750	4270	4790	5320	5840
25	3220	3750	4270	4790	5320	5840
20	3450	4010	4570	5140	5700	6260
5 LT	4320	5030	5730	6440	7140	7840
5 HT	3450	4010	4570	5140	5700	6260

Printed on 24.04.2024 09:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..