

## AGRIMAX RT 855 - Technische Daten



### Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Feldspritze • Traktor •  
Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	420/85 R 34 (16.9 R 34)
LI/SS	147 A8/B

## Dimensions US Standard

Usa code	94058532
Section Width (inch)	17.2
Overall Diameter (inch)	62.1
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	188.3
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E11-106R-005179
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	3200	3670	4210	4750	5290	5830	6380	6780
25	3200	3670	4210	4750	5290	5830	6380	6780
20	3420	3920	4510	5090	5680	6250	6830	7260
5 LT	4280	4920	5640	6370	7100	7830	8550	9090
5 HT	3420	3920	4510	5090	5680	6250	6830	7260

Printed on 24.04.2024 11:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..