

## AGRIMAX RT 855 - Technische Daten



### Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Feldspritze • Traktor •  
Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	480/80 R 42 (18.4 R 42)
LI/SS	151 A8/B

## Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1835
Static Loaded Radius (mm)	835
Rolling Circumference (mm)	5495
SRI (mm)	875
Rim Rec	W 16 A ; DD 16 ; DW 16 A
Rim Alt	DD 16 L ; DW 16 L ; W 16 L
ECE	E4-106R-000791
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1900	2210	2520	2830	3140	3450
40	1900	2210	2520	2830	3140	3450
30	2035	2365	2700	3030	3365	3695
10 LT	2545	2960	3380	3795	4210	4625
10 HT	2035	2365	2700	3030	3365	3695

Printed on 24.04.2024 12:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..