

## AGRIMAX RT 855 - Technische Daten



### Description

AGRIMAX RT 855 zeichnet sich durch ausgezeichnete Traktion und besonderen Fahrkomfort aus. Hauptsächlich zur Bodenbearbeitung sowie Straßen- und Feldtransport entwickelt eignen sich einige Größen auch für Sprühanwendungen und die Weinlese. AGRIMAX RT 855 ist ein Reifen mit hervorragenden Selbstreinigungseigenschaften, die einen raschen Wechsel von Operationen auf dem Feld zum Einsatz auf der Straße erlauben.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Feldspritze • Traktor •  
Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	480/80 R 46 (18.4 R 46)
LI/SS	158 A8/B

## Dimensions US Standard

Usa code	94021826
Section Width (inch)	18.9
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	35.2
Rolling Circumference (inch)	231.1
Rim Rec	DW 16 A ; W 16 A ; DD 16
Rim Alt	W 16 L ; DD 16 L ; DW 16 L
ECE	E4-106R-001731
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	4410	5060	5810	6560	7310	8060	8720	9350
25	4410	5060	5810	6560	7310	8060	8720	9350
20	4720	5420	6230	7020	7830	8630	9340	10030
5 LT	5910	6790	7790	8800	9800	10800	11680	12550
5 HT	4720	5420	6230	7020	7830	8630	9340	10030

Printed on 24.04.2024 07:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..