

## AGRIMAX RT 945 - Technische Daten



### Description

AGRIMAX RT 945 wurde speziell für Reihenkulturen entwickelt: Er beschädigt die Kulturen nicht, sondern schützt die Ernte. Ferner ermöglichen seine hervorragenden Selbstreinigungseigenschaften den raschen Wechsel zwischen Feldarbeiten und Straßeneinsatz, wo AGRIMAX RT 945 brillante Leistungen zeigt. Seine robuste Karkasse verleiht dem Reifen ausgezeichnete Stabilität, erstklassige Traktion und außerordentliche Beständigkeit.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Feldspritze • Traktor

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 380/90 R 46<br>(14.9 R 46) |
| LI/SS     | 159 A8/B                   |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 380            |
| Overall Diameter (mm)      | 1852           |
| Static Loaded Radius (mm)  | 859            |
| Rolling Circumference (mm) | 5699           |
| SRI (mm)                   | 875            |
| Rim Rec                    | W 12           |
| Rim Alt                    | W 11 ; W 13    |
| ECE                        | E4-106R-001409 |
| TRA Code                   | R1W            |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50         | 1785 | 2290 | 2790 | 3065 | 3295 | 3605 | 3875 | 4070 | 4375 | -    |
| 40         | 1785 | 2290 | 2790 | 3065 | 3295 | 3605 | 3875 | 4070 | 4375 | -    |
| 30         | 1910 | 2450 | 2990 | 3280 | 3530 | 3860 | 4150 | 4360 | 4685 | -    |
| 10         | 2095 | 2735 | 3315 | 3955 | 4540 | 4715 | 5235 | 5815 | 6040 | 6565 |

Printed on 17.04.2024 05:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..