

AGRIMAX RT 945 - Technische Daten



Description

AGRIMAX RT 945 wurde speziell für Reihenkulturen entwickelt: Er beschädigt die Kulturen nicht, sondern schützt die Ernte. Ferner ermöglichen seine hervorragenden Selbstreinigungseigenschaften den raschen Wechsel zwischen Feldarbeiten und Straßeneinsatz, wo AGRIMAX RT 945 brillante Leistungen zeigt. Seine robuste Karkasse verleiht dem Reifen ausgezeichnete Stabilität, erstklassige Traktion und außerordentliche Beständigkeit.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor

Version	STANDARD
Type	TL
Tyre Size	380/90 R 50 (14.9 R 50)
LI/SS	151 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1954
Static Loaded Radius (mm)	913
Rolling Circumference (mm)	5902
SRI (mm)	950
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-001487
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8
50	1865	2415	2970	3210	3450	-
40	1865	2415	2970	3210	3450	-
30	2000	2590	3180	3440	3695	-
10	2745	3365	4090	4765	5020	5175

Printed on 27.03.2023 13:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..