

AGRIMAX RT 945 - Technische Daten



Description

AGRIMAX RT 945 wurde speziell für Reihenkulturen entwickelt: Er beschädigt die Kulturen nicht, sondern schützt die Ernte. Ferner ermöglichen seine hervorragenden Selbstreinigungseigenschaften den raschen Wechsel zwischen Feldarbeiten und Straßeneinsatz, wo AGRIMAX RT 945 brillante Leistungen zeigt. Seine robuste Karkasse verleiht dem Reifen ausgezeichnete Stabilität, erstklassige Traktion und außerordentliche Beständigkeit.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor

Version	STANDARD
Type	TL
Tyre Size	380/90 R 50 (14.9 R 50)
LI/SS	160A8/B

Dimensions International Standard

Section Width (mm)	390
Overall Diameter (mm)	1954
Static Loaded Radius (mm)	921
Rolling Circumference (mm)	5958
SRI (mm)	925
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E11-106R-006446
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1845	2385	2880	3195	3375	3690	4005	4275	4500	---
40	1845	2385	2880	3195	3375	3690	4005	4275	4500	---
30	1975	2555	3085	3420	3615	3950	4290	4575	4815	---
10	2670	3450	4165	4620	4880	5335	5790	6180	6505	6750

Printed on 17.04.2024 04:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..