

AGRIMAX RT 945 - Datenblatt



Description

AGRIMAX RT 945 wurde speziell für Reihenkulturen entwickelt: Er beschädigt die Kulturen nicht, sondern schützt die Ernte. Ferner ermöglichen seine hervorragenden Selbstreinigungseigenschaften den raschen Wechsel zwischen Feldarbeiten und Straßeneinsatz, wo AGRIMAX RT 945 brillante Leistungen zeigt. Seine robuste Karkasse verleiht dem Reifen ausgezeichnete Stabilität, erstklassige Traktion und außerordentliche Beständigkeit.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Feldspritze • Traktor

| SIZE | Version | USACode | TRA Code | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|------------------------------------|----------|----------|----------|--------------|---------|-------------|------|------|------|-------|------|-----------------|
| 420/90 R 30 | STANDARD | 94063857 | R1W | 147 A8/B | DW13 | W 14 L | 16.5 | 59.8 | 26.9 | 180 | TL | E11-106R-006021 |
| 320/90 R 42 (12.4 R 42) | STANDARD | 94038664 | R1W | 139 A8/B | W 10 | W 9 ; W 11 | 12.6 | 64.7 | 29.9 | 194.6 | TL | E4-106R-000783 |
| 320/90 R 46 (12.4 R 46) | STANDARD | 94051694 | R1W | 148 D/151 A8 | W 10 | W 9 ; W 11 | 12.6 | 68.7 | 31.9 | 206 | TL | E11-106R-004068 |
| 320/90 R 46 (12.4 R 46) | STANDARD | 94044719 | R1W | 146 A8/B | W 10 | W 9 ; W 11 | 12.6 | 68.7 | 31.9 | 206 | TL | E4-106R-001399 |
| 380/90 R 46 (14.9 R 46) | STANDARD | 94040551 | R1W | 155 A8/B | W 12 | W 11 ; W 13 | 15 | 72.9 | 33.8 | 220.3 | TL | E4-106R-00797 |
| 380/90 R 46 (14.9 R 46) | STANDARD | 94021833 | R1W | 159 A8/B | W 12 | W 11 ; W 13 | 15 | 72.9 | 33.8 | 224.4 | TL | E4-106R-001409 |
| 320/90 R 50 (12.4 R 50) | STANDARD | 94037612 | R1W | 150 A8/B | W 10 | W 9 ; W 11 | 12.6 | 72.7 | 34.4 | 221.2 | TL | E4-106R-000787 |
| 380/90 R 50 (14.9 R 50) | STANDARD | 94037025 | R1W | 151 A8/B | W 12 | W 11 ; W 13 | 15 | 76.9 | 35.9 | 232.4 | TL | E4-106R-001487 |
| 380/90 R 50 (14.9 R 50) | STANDARD | 94065479 | R1W | 160A8/B | W 12 | W 11 ; W 13 | 15.4 | 76.9 | 36.3 | 234.6 | TL | E11-106R-006446 |
| 320/90 R 54 (12.4 R 54) | STANDARD | 94037094 | R1W | 156 A8/B | W 10 | W 9 ; W 11 | 12.6 | 76.7 | 36.6 | 237 | TL | E11-106R-003474 |
| 380/90 R 54 (14.9 R 54) | STANDARD | 94046799 | R1W | 158 A8/B | W 12 | W 11 ; W 13 | 15 | 80.9 | 37.9 | 247.9 | TL | E4-106R-001488 |

Printed on 27.03.2023 12:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..