

AGRIMAX RT 955 - Technische Daten



Description

AGRIMAX RT 955 ist ein idealer BKT Radialreifen für Reihenkulturen, während sich einige Größen auch für Sprühanwendungen eignen. Das spezielle Laufflächendesign mit abgerundeter Schulter gewährleistet hervorragende Traktionsleistungen, Stabilität und Selbstreinigungseigenschaften. Dank seiner robusten Karkasse bietet AGRIMAX RT 955 eine hohe Tragfähigkeit.

UM

International Standard

Construction

RADIAL

Machinery

Landwirtschaft: Feldspritze, Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	210/95 R 32 (8.3 R 32)
LI/SS	120 A8/B

Dimensions International Standard

Section Width (mm)	214
Overall Diameter (mm)	1213
Static Loaded Radius (mm)	571
Rolling Circumference (mm)	3703
SRI (mm)	575
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001391
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	645	830	1010	1095	1190	1305	1400	-
40	645	830	1010	1095	1190	1305	1400	-
30	690	885	1080	1170	1275	1395	1500	-
10	905	1180	1430	1555	1660	1830	1975	2100

Printed on 19.08.2022 19:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..