

AGRIMAX RT 955 - Technische Daten



Description

AGRIMAX RT 955 ist ein idealer BKT Radialreifen für Reihenkulturen, während sich einige Größen auch für Sprühanwendungen eignen. Das spezielle Laufflächendesign mit abgerundeter Schulter gewährleistet hervorragende Traktionsleistungen, Stabilität und Selbstreinigungseigenschaften. Dank seiner robusten Karkasse bietet AGRIMAX RT 955 eine hohe Tragfähigkeit.

UM

International Standard

Construction

RADIAL

Machinery

Landwirtschaft: Feldspritze, Traubenerntemaschine

| | |
|-----------|---------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 230/95 R 40 (9.5 R 40) |
| LI/SS | 132 A8/B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 228 |
| Overall Diameter (mm) | 1454 |
| Static Loaded Radius (mm) | 690 |
| Rolling Circumference (mm) | 4445 |
| SRI (mm) | 700 |
| Rim Rec | W 7 |
| Rim Alt | W 8 |
| ECE | E11-106R-004066 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50 | 820 | 1060 | 1280 | 1420 | 1500 | 1640 | 1780 | 1900 | 2000 | - |
| 40 | 820 | 1060 | 1280 | 1420 | 1500 | 1640 | 1780 | 1900 | 2000 | - |
| 30 | 880 | 1135 | 1370 | 1520 | 1605 | 1755 | 1905 | 2035 | 2140 | - |
| 10 | 930 | 1170 | 1440 | 1710 | 1980 | 2040 | 2280 | 2520 | 2760 | 3000 |

Printed on 19.08.2022 19:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..