

AGRIMAX RT 955 - Technische Daten



Description

AGRIMAX RT 955 ist ein idealer BKT Radialreifen für Reihenkulturen, während sich einige Größen auch für Sprühanwendungen eignen. Das spezielle Laufflächendesign mit abgerundeter Schulter gewährleistet hervorragende Traktionsleistungen, Stabilität und Selbstreinigungseigenschaften. Dank seiner robusten Karkasse bietet AGRIMAX RT 955 eine hohe Tragfähigkeit.

UM

International Standard

Construction

RADIAL

Machinery

Landwirtschaft: Feldspritze, Traubenerntemaschine

Version	STANDARD
Type	TL
Tyre Size	270/95 R 54 (11.2 R 54)
LI/SS	146 A8/B

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1885
Static Loaded Radius (mm)	894
Rolling Circumference (mm)	5815
SRI (mm)	925
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-001410
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1170	1530	1860	2040	2160	2370	2580	2790	3000	-
40	1170	1530	1860	2040	2160	2370	2580	2790	3000	-
30	1255	1640	1995	2185	2315	2540	2765	2990	3210	-
10	1395	1755	2160	2565	2970	3060	3420	3780	4140	4500

Printed on 19.08.2022 19:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..