

## AGRIMAX TURF RT 333 - Datenblatt



### Description

Der AGRIMAX TURF RT 333 (R-3+) ist ein Radialreifen, der für kleine Traktoren bei Anwendungen im Garten-, Wein- und Obstbau entwickelt wurde. Sein abgerundetes Schulterdesign sorgt für eine geringe Bodenverdichtung und macht ihn äußerst empfindlich auf dem Boden. Sein einzigartiges extratiefes Profil (R-3+) und das spezielle Design mit laufrichtungsgebundenen Blöcken stehen für eine ausgezeichnete Traktion sowohl auf dem Feld als auch auf der Straße und eine verlängerte Lebensdauer des Reifens. AGRIMAX TURF RT 333 (R-3+) gewährleistet große Selbstreinigungseigenschaften und ermöglicht dank seines geringen Rollwiderstands eine erhebliche Kraftstoffeinsparung.

### UM

US Standard

### Construction



RADIAL

### Machinery

Landwirtschaft: Erntemaschine für Obst • Kleintraktor • Traubenerntemaschine

| SIZE       | Version  | USACode  | TRA Code | LI/SS          | RIM REC | RIM ALT         | SW   | OD   | SLR  | RC    | Type | ECE              |
|------------|----------|----------|----------|----------------|---------|-----------------|------|------|------|-------|------|------------------|
| 220/55 R12 | STANDARD | 94070237 |          | 82 A8/B        | 7       |                 | 8.7  | 21.7 | 9.8  | 64.8  | TL   | E11-106R-007600  |
| 240/60 R12 | STANDARD | 94070657 |          | 89 A8/B        | 7       |                 | 9.5  | 23.3 | 10.6 | 70    | TL   | E11-106R-007679  |
| 215/65 R14 | STANDARD | 94076277 |          | 90 A8 / 90 B   | W 7     | W 6             | 8.7  | 24.8 | 11.4 | 75    | TL   | E11-106R-0010331 |
| 200/65 R16 | STANDARD | 94070640 |          | 94 A8/B        | W6      |                 | 8    | 26.2 | 12.2 | 78.7  | TL   | E11-106R-007678  |
| 200/70 R16 | STANDARD | 94074136 | R1W      | 94 A8/B        | W 6     |                 | 7.9  | 27   | 12.5 | 80.9  | TL   | E11-106R-008659  |
| 240/70 R16 | STANDARD | 94070282 |          | 104 A8/B       | W8      | W 8 L ; W 9     | 9.6  | 29.2 | 13.4 | 87.1  | TL   | E11-106R-007531  |
| 260/70 R16 | STANDARD | 94067909 |          | 109 A8/109 B   | W 8     | W 8 L ; W 9     | 10.2 | 30.3 | 13.7 | 90    | TL   | E11-106R-007158  |
| 280/70 R16 | STANDARD | 94065714 |          | 112 A8/112 B   | W9      | W 8 ; W 10      | 11.4 | 31.5 | 14.1 | 93.3  | TL   | E11-106R-006472  |
| 280/70 R18 | STANDARD | 94065707 |          | 114 A8/114 B   | W 9     | W 8 ; W 10      | 11.4 | 33.1 | 15.4 | 100.4 | TL   | E11-106R-006473  |
| 320/65 R18 | STANDARD | 94071081 |          | 109 A8/109 B   | W 10    | W 9 ; W 11      | 12.6 | 34.4 | 15.5 | 102   | TL   | E11-106R-007844  |
| 300/70 R20 | STANDARD | 9406748  |          | 110 A8/110 B   | W9      | W10             | 11.6 | 37.5 | 17   | 111.3 | TL   | E11-106R-006943  |
| 320/70 R20 | STANDARD | 94067558 |          | 113 A8/113 B   | W10     | W9 ; W11        | 12.6 | 38.7 | 17.4 | 114.8 | TL   | E11-106R-006944  |
| 380/70 R20 | STANDARD | 94068821 |          | 122 A8/122 B   | W 12    | W 11 ; W 13     | 15   | 42.6 | 19.1 | 126.5 | TL   | E11-106R-007111  |
| 360/70 R24 | STANDARD | 94067916 |          | 122 A8/122 B   | W 11    | W 10 ; W 12     | 14.1 | 45.4 | 20.4 | 134.2 | TL   | E11-106R-007110  |
| 380/70 R24 | STANDARD | 94068838 |          | 125 A8/125 B   | W 12    | W 11 ; W 13     | 15   | 46.9 | 21   | 139.3 | TL   | E11-106R-007112  |
| 420/70 R24 | STANDARD | 94069460 |          | 130 A8 / 130 B | W 13    | W 12 ; W 14 L   | 16.5 | 49.1 | 21.9 | 146.8 | TL   | E11-106R-007206  |
| 420/85 R24 | STANDARD | 94501649 |          | 137 A8 / 137 B | W 15 L  | DW15L;DW14L     | 17.1 | 52.1 | 23.4 | 155.8 | TL   | E11-106R-0010344 |
| 340/85 R28 | STANDARD | 94076390 |          | 127 A8 / 127 B | W 12    | W11;DW11;DW12   | 14.6 | 50.7 | 23   | 152.5 | TL   | E11-106R-0010343 |
| 480/70 R28 | STANDARD | 94075393 |          | 140 A8 / 140 B | W 15 L  | W 14 L ; W 16 L | 18.9 | 55.9 | 24.8 | 166.5 | TL   | E11-106R-009049  |
| 480/70 R30 | STANDARD | 94075409 |          | 141 A8 / 141 B | W 15 L  | W 14 L ; W 16 L | 18.9 | 58.2 | 26   | 173.1 | TL   | E11-106R-009050  |
| 480/70 R34 | STANDARD | 94075232 |          | 149 A8 / 149 B | W 15 L  | W 14 L ; W 16 L | 19.3 | 62.2 | 28.5 | 188.4 | TL   | E11-106R-009042  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 04.05.2025 01:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..