AGRIMAXFACTOR - Technische Daten

Description

AGRIMAXFACTOR ist BKTs brandneuer Reifen der 70er Serie für Traktoren, der sowohl für den Transport als auch zur Bodenbearbeitung perfekt ist. Das verbesserte Laufflächendesign mit größerer Länge und geänderter Orientierung der Stollen steht für bessere Fahreigenschaften. Der reduzierte Stollenwinkel einen geringeren Rollwiderstand, während die um 5% vergrößerte Kontaktfläche auf dem Land das subjektive Lärmempfinden in der Fahrerkabine reduziert – beide Eigenschaften stehen für mehr Komfort. Außerdem verleiht die robuste Polyesterkarkasse ausgezeichnete seitliche Stabilität neben raschem Lenkansprechen auch bei hohen Geschwindigkeiten oder im Schwersteinsatz. Die Bremsergebnisse des Reifens auf nasser Oberfläche sind hervorragend.
Kurzum, AGRIMAXFACTORs Hauptvorteile sind großartiges Handling kombiniert mit unter vielen Aspekten außergewöhnlichem Fahrkomfort neben exzellenter Beständigkeit – alles besondere Anforderungen immer schwererer Maschinen und nicht zuletzt des höheren Gewichts der Batteriepakete von E-Fahrzeugen. Die exklusive Flanke zeigt das perfekt ausgerichtete “E-READY”-Logo, welches BKTs Verpflichtung zur elektrischen Mobilität unterstreicht.

UM

International Standard

Construction

RADIAL

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TL
Tyre Size	520/70 R 38

LI/SS	150 D/153 A8

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1749
Static Loaded Radius (mm)	795
Rolling Circumference (mm)	5239
SRI (mm)	825
Rim Rec	W 16 L
Rim Alt	W 15 L ; W 18 L
ECE	E11-106R-007609
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1845	2145	2450	2750	3050	3350
50	1940	2255	2570	2890	3205	3520
40	2020	2350	2680	3010	3340	3670
30	2125	2470	2815	3165	3510	3855
10 LT	2470	2875	3280	3685	4090	4490
10 HT	2125	2470	2815	3165	3510	3855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13.05.2025 07:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..