

## AIROMAX AM 27 - Technische Daten



### Description

AIROMAX AM 27 ist ein Radialreifen zum überwiegenden Straßeneinsatz, ideal für Krananwendungen im Baugewerbe. Der Reifen zeichnet sich durch besondere Hitzebeständigkeit und ausgezeichneten Fahrkomfort aus. AIROMAX AM 27 ist ein Hochgeschwindigkeitsreifen, der sich speziell für alle Arbeiten eignet, die einen hohen Level ein Manövrierbarkeit verlangen.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrie: Mobilkran

Version	STANDARD
Type	TL
Tyre Size	445/95 R 25 (16.00 R 25)
LI/SS	174 F

## Dimensions US Standard

Usa code	94039043
Overall Width (inch)	17.3
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	27.4
Rolling Circumference (inch)	180.6
Rim Rec	11.25/2.0
Rim Alt	11.00/1.7 CR ; 11.00/1.7CRL
ECE	E4-54R-0028867

## Load capacity (lbs)

mph / psi	130
20	18700
25	17100
30	16500
35	16100
43	15700
50	14800
55	13900
62	12300

Printed on 18.04.2024 03:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..