

AIROMAX AM 27 - Technische Daten



Description

AIROMAX AM 27 ist ein Radialreifen zum überwiegenden Straßeneinsatz, ideal für Krananwendungen im Baugewerbe. Der Reifen zeichnet sich durch besondere Hitzebeständigkeit und ausgezeichneten Fahrkomfort aus. AIROMAX AM 27 ist ein Hochgeschwindigkeitsreifen, der sich speziell für alle Arbeiten eignet, die einen hohen Level ein Manövrierbarkeit verlangen.

UM

US Standard

Construction

 RADIAL

Machinery

Industrie: Mobilkran

Version	STANDARD
Type	TL
Tyre Size	505/95 R 25 (18.00 R 25)
LI/SS	186 E

Dimensions US Standard

Usa code	94045198
Overall Width (inch)	19.4
Overall Diameter (inch)	63
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	192.9
Rim Rec	13.00/2.5

Load capacity (lbs)

mph / psi	130
20	27200
25	26000
30	24700
35	23500
43	20900
50	17200
55	14700
62	12600

Printed on 18.04.2024 03:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..