

## AIROMAX AM 27 - Technische Daten



### Description

AIROMAX AM 27 ist ein Radialreifen zum überwiegenden Straßeneinsatz, ideal für Krananwendungen im Baugewerbe. Der Reifen zeichnet sich durch besondere Hitzebeständigkeit und ausgezeichneten Fahrkomfort aus. AIROMAX AM 27 ist ein Hochgeschwindigkeitsreifen, der sich speziell für alle Arbeiten eignet, die einen hohen Level ein Manövrierbarkeit verlangen.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrie: Mobilkran

Version	STANDARD
Type	TL
Tyre Size	525/80 R 25 (20.5 R 25)
LI/SS	176 F

## Dimensions International Standard

Overall Width (mm)	530
Overall Diameter (mm)	1481
Static Loaded Radius (mm)	681
Rolling Circumference (mm)	4534
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7 CR
ECE	E11-54R-0016681

## Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
80	5600	5800	6000	6300	6500	6700	6900	7100

Printed on 18.04.2024 04:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..