AIROMAX AM 543 - Technische Daten

Description

AIROMAX AM 543 ist der ideale Reifen für Krananwendungen im Baugewerbe. Er bietet hervorragende Traktion und erstklassige Stabilität. Da Reifen für Kräne besonderen Beanspruchungen und extremen Einsatzbedingungen ausgesetzt sind, wurde AIROMAX AM 543 speziell für ausgezeichnete Hitzebeständigkeit entwickelt. Daneben eignet er sich für alle Arbeiten, die einen hohen Level ein Manövrierbarkeit verlangen.

UM

US Standard

Construction

RADIAL

Machinery

Industrie: Mobilkran

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 E

Dimensions US Standard

Usa code	94064519
Overall Width (inch)	14.8
Overall Diameter (inch)	53.3
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	163.6
Rim Rec	10.00/1.5

Load capacity (lbs)

mph / psi	130
43	13200

Printed on 08.05.2024 03:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..