

AIROMAX AM 543 - Datenblatt



Description

AIROMAX AM 543 ist der ideale Reifen für Krananwendungen im Baugewerbe. Er bietet hervorragende Traktion und erstklassige Stabilität. Da Reifen für Kräne besonderen Beanspruchungen und extremen Einsatzbedingungen ausgesetzt sind, wurde AIROMAX AM 543 speziell für ausgezeichnete Hitzebeständigkeit entwickelt. Daneben eignet er sich für alle Arbeiten, die einen hohen Level ein Manövrierbarkeit verlangen.

UM

International Standard

Construction

 RADIAL

Machinery

Industrie: Mobilkran

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
385/95 R 24 (14.00 R 24)	STANDARD	170 E	10.00W		375	1355	627	4156	TT
385/95 R 25 (14.00 R 25)	STANDARD	170 E	10.00/1.5		375	1355	627	4156	TL
445/95 R 25 (16.00 R 25)	STANDARD	177 E	11.25/2.0	11.00/1.7 CR ; 11.00/1.7CRL	435	1480	670	4502	TL

Printed on 19.04.2024 03:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..