

## AS 504 - Technische Daten



### Description

AS 504 ist ein agro-industrieller Reifen, der hauptsächlich zur Bodenbearbeitung sowie zum Einsatz mit landwirtschaftlichen Geräten und zum Materialtransport entwickelt wurde. Dieser Reifen, der sich durch ausgezeichnete Selbstreinigungseigenschaften und verstärkte Haftung auszeichnet, eignet sich für Feldanhänger und Teleskoplader. Es gibt den AS 504 Reifen in verschiedenen Ausführungen, um den spezifischen Anforderungen der Endnutzer gerecht zu werden: eine „HD“-Ausführung mit besonders schnitt- und reißfester Gummimischung, während die „special“ Ausführung mit verstärkter Karkasse ein längeres Reifenleben gewährleistet.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Teleskoplader • Feld-Anhänger  
Industrie: Teleskoplader

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

## Dimensions US Standard

Usa code	94018628
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.7
Static Loaded Radius (inch)	16.8
Rolling Circumference (inch)	109.8
Rim Rec	W 9
Rim Alt	9 ; W 8
ECE	E4-106R-002325

## Load capacity (lbs)

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Printed on 26.04.2024 10:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..