AS 504 - Technische Daten

Description

AS 504 ist ein agro-industrieller Reifen, der hauptsächlich zur Bodenbearbeitung sowie zum Einsatz mit landwirtschaftlichen Geräten und zum Materialtransport entwickelt wurde. Dieser Reifen, der sich durch ausgezeichnete Selbstreinigungseigenschaften und verstärkte Haftung auszeichnet, eignet sich für Feldanhänger und Teleskoplader. Es gibt den AS 504 Reifen in verschiedenen Ausführungen, um den spezifischen Anforderungen der Endnutzer gerecht zu werden: eine „HD“-Ausführung mit besonders schnitt- und reißfester Gummimischung, während die „special“ Ausführung mit verstärkter Karkasse ein längeres Reifenleben gewährleistet.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: Teleskoplader • Feld-Anhänger
Industrie: Teleskoplader

Version	STANDARD
Type	TL
Tyre Size	16.5/85 - 24
LI/SS DRIVE WHEEL	155 A8
LI/SS FREE ROLLING	168 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	415
Overall Diameter (mm)	1325
Static Loaded Radius (mm)	591
Rolling Circumference (mm)	3837
SRI (mm)	625
Rim Rec	W 13
Rim Alt	W 14 L ; W 15 L

Load capacity (Kg)

km/h / bar	3.80
10 FR	7840
25 FR	6665
30 FR	6270
40 FR	5600
10 DW	5425
25 DW	4610
30 DW	4340
40 DW	3875

Printed on 25.04.2024 17:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..