

AS 505 - Datenblatt



Description

AS 505 ist bestens für die Bodenbearbeitung mit Anhängern und landwirtschaftlichen Geräten geeignet. Er zeichnet sich durch ausgezeichnete Selbstreinigungseigenschaften und verstärkte Traktion auf dem Boden aus, speziell auf Schlamm. Der Reifen gewährleistet auch einen langen Produktlebenszyklus.

UM

US Standard

Construction

BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte, Anhänger

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
6.5/80 - 15	STANDARD	94019472	8	5.0	4½ K ; 5 K ; 5 J	6.7	26.9	12.8	82.9	TL	E4-106R-002660
6.5/80 - 15	STANDARD	94019465	6	5.0	4½ K ; 5 K ; 5 J	6.7	26.9	12.8	82.9	TL	E4-106R-002188

Printed on 20.10.2020 01:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..