

AT 108 - Technische Daten

Description

AT 108 ist ein Geländereifen, der sich bestens für ATV-
Geländefahrzeuge eignet. Das Laufflächendesign
gewährleistet ausgezeichneten Fahrkomfort und beste
Leistung auf und abseits der Straße.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: Geländefahrzeug



Version	STANDARD
Type	TL
Tyre Size	AT 20 X 10 - 10

Dimensions International Standard

Ply Rating	8
Section Width (mm)	250
Overall Diameter (mm)	514
Static Loaded Radius (mm)	235
Rolling Circumference (mm)	1526
Rim Rec	8.0 AT
Rim Alt	7.5 AT ; 8.5 AT

Load capacity (Kg)

km/h / bar	0.55
80	155

Printed on 18.04.2024 23:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..