

## AT 111 HD - Datenblatt



### Description

AT 111 HD eignet sich für ATV-Sport-Rennen mit Geländefahrzeugen. Die verstärkte Tiefe und die Dicke der Flanken bieten ausgezeichnete Haftung und Bremskontrolle sowie hervorragende Traktion und Kontrolle bei hohen Geschwindigkeiten auch bei Übersteuer-Manövern. AT 111 HD gewährleistet ein langes Reifenleben.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Geländefahrzeug

| SIZE            | Version  | LI/SS | PR | RIM REC | RIM ALT | SW  | OD  | Type | ECE            |
|-----------------|----------|-------|----|---------|---------|-----|-----|------|----------------|
| AT 20 X 11 - 9  | STANDARD | 43 J  | 6  | 9.0 AT  | 8.5 AT  | 275 | 515 | TL   | E4-75R-0006326 |
| AT 22 X 11 - 9  | STANDARD |       | 6  | 9.0 AT  | 8.5 AT  | 279 | 560 | TL   | E4-75R-0006332 |
| AT 20 X 11 - 10 | STANDARD |       | 6  | 9.0 AT  | 8.5 AT  | 279 | 505 | TL   | E4-75R-0006327 |
| AT 21 X 7 - 10  | STANDARD | 30 J  | 6  | 5.5 AT  | 6.0 AT  | 178 | 533 | TL   | E4-75R-0006329 |
| AT 22 X 11 - 10 | STANDARD |       | 6  | 9.0 AT  | 8.5 AT  | 279 | 560 | TL   | E4-75R-0006333 |
| AT 22 X 7 - 10  | STANDARD |       | 6  | 5.5 AT  | 6.0 AT  | 174 | 560 | TL   | E4-75R-0006331 |
| AT 23 X 7 - 10  | STANDARD |       | 6  | 5.5 AT  | 6.0 AT  | 174 | 585 | TL   | E4-75R-0006335 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25.03.2025 07:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..