

AT 171 - Technische Daten



Description

AT 171 wurde speziell für Schlammrennen mit Traktoren entwickelt. Das spezielle richtungsgebundene und extra tiefe Laufflächenprofil verleiht hervorragende Traktion auf nassem und schlammigem Gelände.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Geländefahrzeug • Fahrzeug für Schlammrennen

Version	STANDARD
Type	TT
Tyre Size	AT 35 X 10 - 18
LI/SS	90 A8/ 66 F

Dimensions US Standard

Usa code	94053780
Ply Rating	8
Section Width (inch)	9.5
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	16.4
Rolling Circumference (inch)	104.2
Rim Rec	W 8
TRA Code	R1W+

Load capacity (lbs)

	mph / psi	20	15
25 MUD BOGGING		1325	-
50 MUD BOGGING		665	-
25 CASUAL TRANSPORT		-	1080
50 CASUL TRANSPORT		-	540

Printed on 20.04.2024 15:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..